

# True Brand Diesel Max

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Revision Date: 09/16/2015

Date of issue: 09/11/2015

Version: 1.0

## SECTION 1: IDENTIFICATION

### 1.1. Product Identifier

**Product Form:** Mixture

**Product Name:** True Brand Diesel Max

**Product Part #:** T2102

### 1.2. Intended Use of the Product

**Use of the substance/mixture:** Automotive

### 1.3. Name, Address, and Telephone of the Responsible Party

#### Company

Solid Start, Inc.

3705 HWY 98 South

Lakeland, FL 33812

863-937-9297

[www.solidstart.biz](http://www.solidstart.biz)

### 1.4. Emergency Telephone Number

**Emergency Number** : 813-248-0585 ChemTel

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the Substance or Mixture

#### GHS-US classification

Flam. Liq. 2 H225

Acute Tox. 4 (Oral) H302

Skin Irrit. 2 H315

Eye Dam. 1 H318

Skin Sens. 1 H317

Muta. 1B H340

Carc. 1B H350

Repr. 1B H360

STOT SE 3 H336

Asp. Tox. 1 H304

Aquatic Acute 2 H401

Aquatic Chronic 2 H411

Full text of H-phrases: see section 16

### 2.2. Label Elements

#### GHS-US Labeling

##### Hazard Pictograms (GHS-US)

:



GHS02



GHS05



GHS07



GHS08



GHS09

##### Signal Word (GHS-US)

: Danger

##### Hazard Statements (GHS-US)

H225 - Highly flammable liquid and vapor.

H302 - Harmful if swallowed.

H304 - May be fatal if swallowed and enters airways.

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H318 - Causes serious eye damage.

H336 - May cause drowsiness or dizziness.

H340 - May cause genetic defects.

H350 - May cause cancer.

H360 - May damage fertility or the unborn child.

H401 - Toxic to aquatic life.

H411 - Toxic to aquatic life with long lasting effects.

##### Precautionary Statements (GHS-US)

P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

# True Brand Diesel Max

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P210 - Keep away from extremely high or low temperatures, ignition sources, and incompatible materials. - No smoking.  
P240 - Ground/bond container and receiving equipment.  
P241 - Use explosion-proof electrical, ventilating, and lighting equipment.  
P242 - Use only non-sparking tools.  
P243 - Take precautionary measures against static discharge.  
P261 - Avoid breathing vapors, mist, or spray.  
P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.  
P270 - Do not eat, drink or smoke when using this product.  
P271 - Use only outdoors or in a well-ventilated area.  
P272 - Contaminated work clothing must not be allowed out of the workplace.  
P273 - Avoid release to the environment.  
P280 - Wear protective gloves, protective clothing, and eye protection.  
P301+P310 - If swallowed: Immediately call a poison center or doctor.  
P301+P312 - If swallowed: Call a poison center or doctor if you feel unwell.  
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304+P340 - If inhaled: Remove person to fresh air and keep at rest in a position comfortable for breathing.  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P321 - Specific treatment (see section 4 on this SDS).  
P330 - Rinse mouth.  
P331 - Do NOT induce vomiting.  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P370+P378 - In case of fire: Use appropriate media (see section 5) to extinguish.  
P391 - Collect spillage.  
P405 - Store locked up.  
P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.  
P403+P233+P235 - Store in a well-ventilated place. Keep container tightly closed. Keep cool.  
P308+P310+P313 - If exposed or concerned: Get medical advice/attention. Immediately call a poison center or doctor.

### 2.3. Other Hazards

Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions.

### 2.4. Unknown Acute Toxicity (GHS-US)

No data available

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product Identifier	%	GHS-US classification
Solvent naphtha, petroleum, medium aliphatic	(CAS No) 64742-88-7	29.6 - 37	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411

# True Brand Diesel Max

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2-Butoxyethanol	(CAS No) 111-76-2	10-22	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319
2 Ethylhexyl nitrate	(CAS No) 27247-96-7	18 - 50	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2A, H319
Xylenes (o-, m-, p- isomers)	(CAS No) 1330-20-7	8-15	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Asp. Tox. 1, H304 Aquatic Acute 2, H401
Poly(oxy-1,2-ethanediyl), .alpha.-(4-nonylphenyl)-.omega.-hydroxy-, branched	(CAS No) 127087-87-0	3.7 - 11.1	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 3, H412
Acetone	(CAS No) 67-64-1	0.5- 3.7	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Benzene, 1,2,4-trimethyl-	(CAS No) 95-63-6	0.5 - 3.7	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Turpentine, oil	(CAS No) 8006-64-2	0.5-1	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2B, H320 Skin Sens. 1, H317 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Solvent naphtha, petroleum, light aliphatic	(CAS No) 64742-89-8	0.5 - 0.6	Flam. Liq. 1, H224 Skin Irrit. 2, H315 Muta. 1B, H340 Carc. 1B, H350 Repr. 2, H361 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411

# True Brand Diesel Max

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Toluene	(CAS No) 108-88-3	0.1-0.5	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 3, H412
HiTEC®6431 Fuel additive	(CAS No) N/A	0.1- 2	Flam. Liq. 3, H226 Carc. 2, H351 STOT SE 3, H336 STOT SE 3, H335 Asp. Tox. 1, H304
Ethylbenzene	(CAS No) 100-41-4	0.1 - 0.15	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation:vapour), H332 Carc. 2, H351 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 3, H412
1-Methyl-2-pyrrolidone	(CAS No) 872-50-4	0.05 - 0.1	Flam. Liq. 4, H227 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Repr. 1B, H360 STOT SE 3, H335
Proprietary Component one	(CAS No) Proprietary	3-7	Not classified

\*The specific chemical identity and/or exact percentage of composition have been withheld as a trade secret.

Full text of H-phrases: see section 16

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of First Aid Measures

**First-aid Measures General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

**First-aid Measures After Inhalation:** When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

**First-aid Measures After Skin Contact:** Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation develops or persists.

**First-aid Measures After Eye Contact:** Rinse cautiously with water for at least 60 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

**First-aid Measures After Ingestion:** Do NOT induce vomiting. Rinse mouth. Immediately call a POISON CENTER or doctor/physician.

### 4.2. Most important symptoms and effects, both acute and delayed

**Symptoms/Injuries:** Causes skin irritation. May cause drowsiness and dizziness. Harmful if swallowed. Causes serious eye damage. Skin sensitization. May cause genetic defects. May cause cancer. May damage fertility. May damage the unborn child. May be fatal if swallowed and enters airways.

**Symptoms/Injuries After Inhalation:** High concentrations may cause central nervous system depression such as dizziness, vomiting, numbness, drowsiness, headache, and similar narcotic symptoms.

**Symptoms/Injuries After Skin Contact:** Redness, pain, swelling, itching, burning, dryness, and dermatitis. May cause an allergic skin reaction.

**Symptoms/Injuries After Eye Contact:** Causes permanent damage to the cornea, iris, or conjunctiva.

**Symptoms/Injuries After Ingestion:** This material is harmful orally and can cause adverse health effects or death in significant amounts. Aspiration into the lungs can occur during ingestion or vomiting and may cause lung injury.

**Chronic Symptoms:** May cause genetic defects. May cause cancer. May damage fertility or the unborn child.

### 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

# True Brand Diesel Max

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 5: FIRE-FIGHTING MEASURES

#### 5.1. Extinguishing Media

**Suitable Extinguishing Media:** Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO<sub>2</sub>). Water may be ineffective but water should be used to keep fire-exposed container cool.

**Unsuitable Extinguishing Media:** Do not use a heavy water stream. A heavy water stream may spread burning liquid.

#### 5.2. Special Hazards Arising From the Substance or Mixture

**Fire Hazard:** Highly flammable liquid and vapor.

**Explosion Hazard:** May form flammable or explosive vapor-air mixture.

**Reactivity:** Reacts violently with strong oxidizers. Increased risk of fire or explosion.

#### 5.3. Advice for Firefighters

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Use water spray or fog for cooling exposed containers. In case of major fire and large quantities:

Evacuate area. Fight fire remotely due to the risk of explosion.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Other Information:** Do not allow run-off from fire fighting to enter drains or water courses.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Do not get in eyes, on skin, or on clothing. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Use special care to avoid static electric charges. Do not breathe vapor, mist or spray.

##### 6.1.1. For Non-emergency Personnel

**Protective Equipment:** Use appropriate personal protection equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel. Stop leak if safe to do so.

##### 6.1.2. For Emergency Responders

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Ventilate area. Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Eliminate ignition sources.

#### 6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment. Collect spillage.

#### 6.3. Methods and Material for Containment and Cleaning Up

**For Containment:** Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions.

**Methods for Cleaning Up:** Clean up spills immediately and dispose of waste safely. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill. Absorb and/or contain spill with inert material. Do not take up in combustible material such as: saw dust or cellulosic material. Use only non-sparking tools.

#### 6.4. Reference to Other Sections

See Heading 8. Exposure controls and personal protection. See Section 13, Disposal Considerations.

### SECTION 7: HANDLING AND STORAGE

#### 7.1. Precautions for Safe Handling

**Additional Hazards When Processed:** Handle empty containers with care because residual vapors are flammable.

**Precautions for Safe Handling:** Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Take precautionary measures against static discharge. Use only non-sparking tools. Avoid contact with eyes, skin and clothing. Handle empty containers with care because they may still present a hazard. Do not get in eyes, on skin, or on clothing. Do not breathe dust/fume/gas/mist/vapors/spray. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures.

#### 7.2. Conditions for Safe Storage, Including Any Incompatibilities

**Technical Measures:** Comply with applicable regulations. Take action to prevent static discharges. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating, and lighting equipment.

**Storage Conditions:** Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store in a well-ventilated place. Keep container tightly closed. Keep in fireproof place.

**Incompatible Products:** Strong acids, strong bases, strong oxidizers.

#### 7.3. Specific End Use(s)

Automotive

# True Brand Diesel Max

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), or OSHA (PEL).

<b>2-Butoxyethanol (111-76-2)</b>		
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA ACGIH	ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans
USA ACGIH	Biological Exposure Indices (BEI)	200 mg/g Kreatinin (Medium: urine - Time: end of shift - Parameter: Butoxyacetic acid with hydrolysis)
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	24 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (TWA) (ppm)	5 ppm
USA IDLH	US IDLH (ppm)	700 ppm
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	240 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	50 ppm
USA OSHA	Limit value category (OSHA)	prevent or reduce skin absorption
<b>2-Ethylhexyl nitrate (27247-96-7)</b>		
USA OSHA	OSHA PEL (TWA) (ppm)	1 ppm
<b>Acetone (67-64-1)</b>		
USA ACGIH	ACGIH TWA (ppm)	250 ppm
USA ACGIH	ACGIH STEL (ppm)	500 ppm
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA ACGIH	Biological Exposure Indices (BEI)	25 mg/l (Medium: urine - Time: end of shift - Parameter: Acetone (nonspecific))
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	590 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (TWA) (ppm)	250 ppm
USA IDLH	US IDLH (ppm)	2500 ppm (10% LEL)
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	2400 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
<b>Benzene, 1,2,4-trimethyl- (95-63-6)</b>		
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	125 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (TWA) (ppm)	25 ppm
<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>		
USA ACGIH	ACGIH TWA (ppm)	100 ppm
USA ACGIH	ACGIH STEL (ppm)	150 ppm
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA ACGIH	Biological Exposure Indices (BEI)	1.5 g/g Kreatinin (Medium: urine - Time: end of shift - Parameter: Methylhippuric acids)
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm
<b>Turpentine, oil (8006-64-2)</b>		
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA ACGIH	ACGIH chemical category	dermal sensitizer, Not Classifiable as a Human Carcinogen
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	560 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (TWA) (ppm)	100 ppm
USA IDLH	US IDLH (ppm)	800 ppm
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	560 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm
<b>Ethylbenzene (100-41-4)</b>		
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA ACGIH	ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans
USA ACGIH	Biological Exposure Indices (BEI)	0.15 g/g Kreatinin (Medium: urine - Time: end of shift - Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific))
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (TWA) (ppm)	100 ppm

# True Brand Diesel Max

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>USA NIOSH</b>	NIOSH REL (STEL) (mg/m <sup>3</sup> )	545 mg/m <sup>3</sup>
<b>USA NIOSH</b>	NIOSH REL (STEL) (ppm)	125 ppm
<b>USA IDLH</b>	US IDLH (ppm)	800 ppm (10% LEL)
<b>USA OSHA</b>	OSHA PEL (TWA) (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
<b>USA OSHA</b>	OSHA PEL (TWA) (ppm)	100 ppm
<b>1-Methyl-2-pyrrolidone (872-50-4)</b>		
<b>USA ACGIH</b>	Biological Exposure Indices (BEI)	100 mg/l (Medium: urine - Time: end of shift - Parameter: 5-Hydroxy-N-methyl-2-pyrrolidone)
<b>USA AIHA</b>	WEEL TWA (ppm)	10 ppm
<b>USA AIHA</b>	AIHA chemical category	skin notation
<b>2-Butoxyethanol (111-76-2)</b>		
<b>USA ACGIH</b>	ACGIH TWA (ppm)	20 ppm
<b>USA ACGIH</b>	ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans
<b>USA ACGIH</b>	Biological Exposure Indices (BEI)	200 mg/g Kreatinin (Medium: urine - Time: end of shift - Parameter: Butoxyacetic acid with hydrolysis)
<b>USA NIOSH</b>	NIOSH REL (TWA) (mg/m <sup>3</sup> )	24 mg/m <sup>3</sup>
<b>USA NIOSH</b>	NIOSH REL (TWA) (ppm)	5 ppm
<b>USA IDLH</b>	US IDLH (ppm)	700 ppm
<b>USA OSHA</b>	OSHA PEL (TWA) (mg/m <sup>3</sup> )	240 mg/m <sup>3</sup>
<b>USA OSHA</b>	OSHA PEL (TWA) (ppm)	50 ppm
<b>USA OSHA</b>	Limit value category (OSHA)	prevent or reduce skin absorption
<b>Toluene (108-88-3)</b>		
<b>USA ACGIH</b>	ACGIH TWA (ppm)	20 ppm
<b>USA ACGIH</b>	ACGIH chemical category	Not Classifiable as a Human Carcinogen
<b>USA ACGIH</b>	Biological Exposure Indices (BEI)	0.02 mg/l (Medium: blood - Time: prior to last shift of workweek - Parameter: Toluene) 0.03 mg/l (Medium: urine - Time: end of shift - Parameter: Toluene) 0.3 mg/g Kreatinin (Medium: urine - Time: end of shift - Parameter: o-Cresol with hydrolysis (background))
<b>USA NIOSH</b>	NIOSH REL (TWA) (mg/m <sup>3</sup> )	375 mg/m <sup>3</sup>
<b>USA NIOSH</b>	NIOSH REL (TWA) (ppm)	100 ppm
<b>USA NIOSH</b>	NIOSH REL (STEL) (mg/m <sup>3</sup> )	560 mg/m <sup>3</sup>
<b>USA NIOSH</b>	NIOSH REL (STEL) (ppm)	150 ppm
<b>USA IDLH</b>	US IDLH (ppm)	500 ppm
<b>USA OSHA</b>	OSHA PEL (TWA) (ppm)	200 ppm
<b>USA OSHA</b>	OSHA PEL (Ceiling) (ppm)	300 ppm

## 8.2. Exposure Controls

### Appropriate Engineering Controls

: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Gas detectors should be used when flammable gases or vapors may be released. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof equipment.

### Personal Protective Equipment

: Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection. Face shield.



### Materials for Protective Clothing

: Chemically resistant materials and fabrics. Wear fire/flammable resistant/retardant clothing.

### Hand Protection

: Wear protective gloves.

### Eye Protection

: Chemical goggles or face shield.

### Skin and Body Protection

: Wear suitable protective clothing.

# True Brand Diesel Max

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Respiratory Protection</b>	: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.
<b>Other Information</b>	: When using, do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on Basic Physical and Chemical Properties

<b>Physical State</b>	: Liquid
<b>Appearance</b>	: Cloudy
<b>Odor</b>	: No data available
<b>Odor Threshold</b>	: No data available
<b>pH</b>	: No data available
<b>Evaporation Rate</b>	: No data available
<b>Melting Point</b>	: No data available
<b>Freezing Point</b>	: No data available
<b>Boiling Point</b>	: No data available
<b>Flash Point</b>	: >26 °C (78.8 °F)
<b>Auto-ignition Temperature</b>	: No data available
<b>Decomposition Temperature</b>	: No data available
<b>Flammability (solid, gas)</b>	: No data available
<b>Vapor Pressure</b>	: No data available
<b>Relative Vapor Density at 20 °C</b>	: No data available
<b>Relative Density</b>	: No data available
<b>Solubility</b>	: No data available
<b>Partition Coefficient: N-Octanol/Water</b>	: No data available
<b>Viscosity</b>	: No data available

### 9.2. Other Information: No additional information available

## SECTION 10: STABILITY AND REACTIVITY

- 10.1. Reactivity:** Reacts violently with strong oxidizers. Increased risk of fire or explosion.
- 10.2. Chemical Stability:** Extremely flammable liquid and vapor. May form flammable or explosive vapor-air mixture.
- 10.3. Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.
- 10.4. Conditions to Avoid:** Direct sunlight, extremely high or low temperatures, heat, hot surfaces, sparks, open flames, incompatible materials, and other ignition sources.
- 10.5. Incompatible Materials:** Strong acids, strong bases, strong oxidizers.
- 10.6. Hazardous Decomposition Products:** Irritating fumes, smoke, oxides of carbon and hydrocarbons.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on Toxicological Effects

**Acute Toxicity:** Oral: Harmful if swallowed.

<b>True Brand Diesel Max</b>	
<b>ATE (Oral)</b>	1,357.50 mg/kg body weight
<b>Solvent naphtha, petroleum, medium aliphatic (64742-88-7)</b>	
<b>LD50 Oral Rat</b>	> 5000 mg/kg
<b>LD50 Dermal Rabbit</b>	3000 mg/kg
<b>LC50 Inhalation Rat</b>	> 5.28 mg/l/4h
<b>2-Butoxyethanol (111-76-2)</b>	
<b>LD50 Oral Rat</b>	470 mg/kg
<b>LC50 Inhalation Rat</b>	450 ppm/4h
<b>ATE (Dermal)</b>	1,100.00 mg/kg body weight
<b>ATE (Vapors)</b>	11.00 mg/l/4h



# True Brand Diesel Max

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Poly(oxy-1,2-ethanediyl), .alpha.-(4-nonylphenyl)-.omega.-hydroxy-, branched (127087-87-0)</b>	
LD50 Oral Rat	1310 mg/kg
<b>Acetone (67-64-1)</b>	
LD50 Oral Rat	5800 mg/kg
LD50 Dermal Rabbit	15688 mg/kg
LC50 Inhalation Rat	44 g/m <sup>3</sup>
LC50 Inhalation Rat	75.8 mg/l/4h
<b>Benzene, 1,2,4-trimethyl- (95-63-6)</b>	
LD50 Oral Rat	6000 mg/kg
LD50 Dermal Rabbit	> 3160 mg/kg
LC50 Inhalation Rat	18 g/m <sup>3</sup> (Exposure time: 4 h)
LC50 Inhalation Rat	10.8 mg/l/4h
<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rabbit	> 4350 mg/kg
LC50 Inhalation Rat	29.08 mg/l/4h
LC50 Inhalation Rat	6247 ppm/4h (species: Sprague-Dawley)
ATE (Dermal)	1,100.00 mg/kg body weight
ATE (Vapors)	11.00 mg/l/4h
<b>Turpentine, oil (8006-64-2)</b>	
LD50 Oral Rat	4.6 ml/kg
LD50 Dermal Rabbit	> 5010 mg/kg
LC50 Inhalation Rat	12 g/m <sup>3</sup> (Exposure time: 6 h)
LC50 Inhalation Rat	13.7 mg/l/4h
ATE (Oral)	500.00 mg/kg body weight
ATE (Dermal)	1,100.00 mg/kg body weight
<b>Solvent naphtha, petroleum, light aliphatic (64742-89-8)</b>	
LD50 Oral Rat	>= 5000 mg/kg
LD50 Dermal Rabbit	3000 mg/kg
<b>Ethylbenzene (100-41-4)</b>	
LD50 Oral Rat	3500 mg/kg
LD50 Dermal Rabbit	15400 mg/kg
LC50 Inhalation Rat	17.2 mg/l/4h (Exposure time: 4 h)
<b>1-Methyl-2-pyrrolidone (872-50-4)</b>	
LD50 Oral Rat	4150 mg/kg
LD50 Dermal Rabbit	> 5000 mg/kg
LC50 Inhalation Rat	5.1 mg/l/4h
<b>2-Butoxyethanol (111-76-2)</b>	
LD50 Oral Rat	470 mg/kg
LD50 Dermal Rat	220 mg/kg
LD50 Dermal Rabbit	99 mg/kg
LC50 Inhalation Rat	3.84 mg/l/4h
LC50 Inhalation Rat	450 ppm/4h
<b>Toluene (108-88-3)</b>	
LD50 Oral Rat	5580 mg/kg
LD50 Dermal Rabbit	12000 mg/kg
LC50 Inhalation Rat	12.5 mg/l/4h
LC50 Inhalation Rat	25.7 mg/l/4h

**Skin Corrosion/Irritation:** Causes skin irritation.

**Serious Eye Damage/Irritation:** Causes serious eye damage.

**Respiratory or Skin Sensitization:** May cause an allergic skin reaction.

**Germ Cell Mutagenicity:** May cause genetic defects.

**Carcinogenicity:** May cause cancer.

# True Brand Diesel Max

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Solvent naphtha, petroleum, medium aliphatic (64742-88-7)</b>	
<b>National Toxicology Program (NTP) Status</b>	Evidence of Carcinogenicity.
<b>2-Butoxyethanol (111-76-2)</b>	
<b>IARC group</b>	3
<b>Acetone (67-64-1)</b>	
<b>OSHA Specifically Regulated Carcinogen List</b>	In OSHA Specifically Regulated Carcinogen list.
<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
<b>IARC group</b>	3
<b>Ethylbenzene (100-41-4)</b>	
<b>IARC group</b>	2B
<b>National Toxicology Program (NTP) Status</b>	Evidence of Carcinogenicity.
<b>OSHA Hazard Communication Carcinogen List</b>	In OSHA Hazard Communication Carcinogen list.
<b>2-Butoxyethanol (111-76-2)</b>	
<b>IARC group</b>	3
<b>Toluene (108-88-3)</b>	
<b>IARC group</b>	3
<b>Polytetrafluoroethylene (9002-84-0)</b>	
<b>IARC group</b>	3

**Reproductive Toxicity:** May damage fertility or the unborn child.

**Specific Target Organ Toxicity (Single Exposure):** May cause drowsiness or dizziness.

**Specific Target Organ Toxicity (Repeated Exposure):** Not classified

**Aspiration Hazard:** May be fatal if swallowed and enters airways.

**Symptoms/Injuries After Inhalation:** High concentrations may cause central nervous system depression such as dizziness, vomiting, numbness, drowsiness, headache, and similar narcotic symptoms.

**Symptoms/Injuries After Skin Contact:** Redness, pain, swelling, itching, burning, dryness, and dermatitis. May cause an allergic skin reaction.

**Symptoms/Injuries After Eye Contact:** Causes permanent damage to the cornea, iris, or conjunctiva.

**Symptoms/Injuries After Ingestion:** This material is harmful orally and can cause adverse health effects or death in significant amounts. Aspiration into the lungs can occur during ingestion or vomiting and may cause lung injury.

**Chronic Symptoms:** May cause genetic defects. May cause cancer. May damage fertility or the unborn child.

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

**Ecology - General** : Toxic to aquatic life with long lasting effects.

<b>Solvent naphtha, petroleum, medium aliphatic (64742-88-7)</b>	
<b>LC50 Fish 1</b>	800 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
<b>EC50 Daphnia 1</b>	> 100 mg/l (Exposure time: 48 h - Species: Daphnia magna)
<b>2-Butoxyethanol (111-76-2)</b>	
<b>LC50 Fish 1</b>	1490 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
<b>EC50 Daphnia 1</b>	1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)
<b>LC 50 Fish 2</b>	2950 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus)
<b>Acetone (67-64-1)</b>	
<b>LC50 Fish 1</b>	4144.846 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
<b>EC50 Daphnia 1</b>	1679.66 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
<b>LC 50 Fish 2</b>	6210 (6210 - 8120) mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
<b>EC50 Daphnia 2</b>	12600 (12600 - 12700) mg/l (Exposure time: 48 h - Species: Daphnia magna)
<b>Benzene, 1,2,4-trimethyl- (95-63-6)</b>	
<b>LC50 Fish 1</b>	7.19 (7.19 - 8.28) mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
<b>EC50 Daphnia 1</b>	6.14 mg/l (Exposure time: 48 h - Species: Daphnia magna)
<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
<b>LC50 Fish 1</b>	3.3 mg/l
<b>EC50 Daphnia 1</b>	3.82 mg/l (Exposure time: 48 h - Species: water flea)

# True Brand Diesel Max

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

LC 50 Fish 2	2.661 (2.661 - 4.093) mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
NOEC chronic crustacea	1.17
<b>Turpentine, oil (8006-64-2)</b>	
LC50 Fish 1	29 mg/l (Exposure time: 96 h - Species: Danio rerio)
EC50 Daphnia 1	6.4 (Exposure time: 48 h - Species: Daphnia magna)
ErC50 (algae)	17.1 mg/l (Exposure time 72 h - Species: Desmodesmus subspicatus)
<b>Solvent naphtha, petroleum, light aliphatic (64742-89-8)</b>	
LC50 Fish 1	>= 8.2 mg/l Exposure time 96 hour Species: Pimephales promelas
NOEC chronic fish	14 day exposure Species: Pimephales promelas LC50: 5.2 mg/l
<b>Ethylbenzene (100-41-4)</b>	
LC50 Fish 1	11.0 - 18.0 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 1	1.8 - 2.4 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC 50 Fish 2	4.2 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static])
<b>1-Methyl-2-pyrrolidone (872-50-4)</b>	
LC50 Fish 1	832 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 Daphnia 1	4897 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC 50 Fish 2	1072 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
<b>2-Butoxyethanol (111-76-2)</b>	
LC50 Fish 1	1490 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 Daphnia 1	1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC 50 Fish 2	2950 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus)
<b>Toluene (108-88-3)</b>	
LC50 Fish 1	15.22 (15.22 - 19.05) mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	5.46 (5.46 - 9.83) mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC 50 Fish 2	12.6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 2	11.5 mg/l (Exposure time: 48 h - Species: Daphnia magna)
NOEC chronic crustacea	0.74 mg/l (Ceriodaphnia dubia)

## 12.2. Persistence and Degradability

<b>True Brand Diesel Max</b>	
Persistence and Degradability	May cause long-term adverse effects in the environment.
<b>Acetone (67-64-1)</b>	
Persistence and Degradability	Readily biodegradable in water.

## 12.3. Bioaccumulative Potential

<b>True Brand Diesel Max</b>	
Bioaccumulative Potential	Not established.
<b>Solvent naphtha, petroleum, medium aliphatic (64742-88-7)</b>	
BCF fish 1	(bioaccumulation expected)
<b>2-Butoxyethanol (111-76-2)</b>	
Log Pow	0.81 (at 25 °C)
<b>Acetone (67-64-1)</b>	
BCF fish 1	0.69
Log Pow	-0.24
Log Kow	-0.24
<b>Benzene, 1,2,4-trimethyl- (95-63-6)</b>	
Log Pow	3.63
<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
BCF fish 1	0.6 (0.6 - 15)
Log Pow	2.77 - 3.15
<b>Ethylbenzene (100-41-4)</b>	
BCF fish 1	15
Log Pow	3.118

# True Brand Diesel Max

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>1-Methyl-2-pyrrolidone (872-50-4)</b>	
<b>Log Pow</b>	-0.46 (at 25 °C)
<b>2-Butoxyethanol (111-76-2)</b>	
<b>Log Pow</b>	0.81 (at 25 °C)
<b>Toluene (108-88-3)</b>	
<b>Log Pow</b>	2.65

**12.4. Mobility in Soil:** No additional information available

### 12.5. Other Adverse Effects

**Other Information** : Avoid release to the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

**Waste Disposal Recommendations:** Dispose of contents/container in accordance with local, regional, national, and international regulations.

**Additional Information:** Handle empty containers with care because residual vapors are flammable.

**Ecology – Waste Materials:** Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

## SECTION 14: TRANSPORT INFORMATION

### 14.1. In Accordance with DOT

**Proper Shipping Name** : FLAMMABLE LIQUIDS, N.O.S. (Solvent naphtha, petroleum, medium aliphatic and Xylenes (o-, m-, p- isomers))

**Hazard Class** : 3

**Identification Number** : UN1993

**Label Codes** : 3

**Packing Group** : III

**Marine Pollutant** : Marine pollutant



### 14.2. In Accordance with IMDG

**Proper Shipping Name** : FLAMMABLE LIQUID, N.O.S. (Solvent naphtha, petroleum, medium aliphatic and Xylenes (o-, m-, p- isomers))

**Hazard Class** : 3

**Identification Number** : UN1993

**Packing Group** : III

**Label Codes** : 3

**EmS-No. (Fire)** : F-E

**EmS-No. (Spillage)** : S-E

**Marine Pollutant** : Marine pollutant



### 14.3. In Accordance with IATA

**Proper Shipping Name** : FLAMMABLE LIQUID, N.O.S. (Solvent naphtha, petroleum, medium aliphatic and Xylenes (o-, m-, p- isomers))

**Packing Group** : III

**Identification Number** : UN1993

**Hazard Class** : 3

**Label Codes** : 3

**ERG Code (IATA)** : 3H



## SECTION 15: REGULATORY INFORMATION

### 15.1 US Federal Regulations

<b>True Brand Diesel Max</b>	
<b>SARA Section 311/312 Hazard Classes</b>	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard
<b>Solvent naphtha, petroleum, medium aliphatic (64742-88-7)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

# True Brand Diesel Max

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>2-Butoxyethanol (111-76-2)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Poly(oxy-1,2-ethanediyl), .alpha.-(4-nonylphenyl)-.omega.-hydroxy-, branched (127087-87-0)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Acetone (67-64-1)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>EPA TSCA Regulatory Flag</b>	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
<b>Benzene, 1,2,4-trimethyl- (95-63-6)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Subject to reporting requirements of United States SARA Section 313	
<b>SARA Section 313 - Emission Reporting</b>	1.0 %
<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Subject to reporting requirements of United States SARA Section 313	
<b>RQ (Reportable quantity, section 304 of EPA's List of Lists)</b>	100 lb
<b>SARA Section 311/312 Hazard Classes</b>	Delayed (chronic) health hazard Fire hazard Immediate (acute) health hazard
<b>SARA Section 313 - Emission Reporting</b>	1.0 %
<b>Turpentine, oil (8006-64-2)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Solvent naphtha, petroleum, light aliphatic (64742-89-8)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Ethylbenzene (100-41-4)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Subject to reporting requirements of United States SARA Section 313	
<b>RQ (Reportable quantity, section 304 of EPA's List of Lists)</b>	1000 lb
<b>SARA Section 313 - Emission Reporting</b>	0.1 %
<b>1-Methyl-2-pyrrolidone (872-50-4)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Subject to reporting requirements of United States SARA Section 313	
<b>EPA TSCA Regulatory Flag</b>	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
<b>SARA Section 313 - Emission Reporting</b>	1.0 %
<b>2-Butoxyethanol (111-76-2)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Toluene (108-88-3)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Subject to reporting requirements of United States SARA Section 313	
<b>RQ (Reportable quantity, section 304 of EPA's List of Lists)</b>	1000 lb
<b>SARA Section 313 - Emission Reporting</b>	1.0 %
<b>Polytetrafluoroethylene (9002-84-0)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

## 15.2 US State Regulations

<b>Ethylbenzene (100-41-4)</b>	
<b>U.S. - California - Proposition 65 - Carcinogens List</b>	WARNING: This product contains chemicals known to the State of California to cause cancer.
<b>1-Methyl-2-pyrrolidone (872-50-4)</b>	
<b>U.S. - California - Proposition 65 - Developmental Toxicity</b>	WARNING: This product contains chemicals known to the State of California to cause birth defects.

# True Brand Diesel Max

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Toluene (108-88-3)</b>	
<b>U.S. - California - Proposition 65 - Developmental Toxicity</b>	WARNING: This product contains chemicals known to the State of California to cause birth defects.
<b>Solvent naphtha, petroleum, medium aliphatic (64742-88-7)</b>	
U.S. - New Jersey - Right to Know Hazardous Substance List	
<b>2-Butoxyethanol (111-76-2)</b>	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) List	
<b>Acetone (67-64-1)</b>	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List	
U.S. - Pennsylvania - RTK (Right to Know) List	
<b>Benzene, 1,2,4-trimethyl- (95-63-6)</b>	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List	
U.S. - Pennsylvania - RTK (Right to Know) List	
<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List	
U.S. - Pennsylvania - RTK (Right to Know) List	
<b>Turpentine, oil (8006-64-2)</b>	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
<b>Ethylbenzene (100-41-4)</b>	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List	
U.S. - Pennsylvania - RTK (Right to Know) List	
<b>1-Methyl-2-pyrrolidone (872-50-4)</b>	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) List	
<b>2-Butoxyethanol (111-76-2)</b>	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) List	
<b>Toluene (108-88-3)</b>	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List	
U.S. - Pennsylvania - RTK (Right to Know) List	
<b>Polytetrafluoroethylene (9002-84-0)</b>	
U.S. - Pennsylvania - RTK (Right to Know) List	

## SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date	: 09/16/2015
Other Information	: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

# True Brand Diesel Max

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### GHS Full Text Phrases:

Acute Tox. 2 (Dermal)	Acute toxicity (dermal) Category 2
Acute Tox. 3 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Asp. Tox. 1	Aspiration hazard Category 1
Carc. 1B	Carcinogenicity Category 1B
Carc. 2	Carcinogenicity Category 2
Comb. Dust	Combustible Dust
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Eye Irrit. 2B	Serious eye damage/eye irritation Category 2B
Flam. Liq. 1	Flammable liquids Category 1
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 3	Flammable liquids Category 3
Flam. Liq. 4	Flammable liquids Category 4
Muta. 1B	Germ cell mutagenicity Category 1B
Repr. 1B	Reproductive toxicity Category 1B
Repr. 2	Reproductive toxicity Category 2
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization Category 1
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H224	Extremely flammable liquid and vapor
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H227	Combustible liquid
H232	May form combustible dust concentrations in air
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H310	Fatal in contact with skin
H312	Harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H320	Causes eye irritation
H331	Toxic if inhaled
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H340	May cause genetic defects
H350	May cause cancer
H351	Suspected of causing cancer
H360	May damage fertility or the unborn child
H361	Suspected of damaging fertility or the unborn child

# True Brand Diesel Max

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

H373	May cause damage to organs through prolonged or repeated exposure
H401	Toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*

SDS US (GHS HazCom)